


## Serrated Washers

Available in Stainless Steel as standard, these "shake-proof" Serrated Washers fitted internally to the equipment and before a locknut act as an anti-vibration device to prevent the cable gland or other cable entry device and locknut arrangement from inadvertently loosening in service.

**Note:** Alternative materials are also available. Please refer to Table "E" of the Ordering References page detailed below. e.g. 20SW4 for M20 Stainless Steel Serrated Washer, 050NPTSW4 for 1/2" NPT Stainless Steel Serrated Washer.



## Metric Serrated Washers Table

Metric - Serrated Washers			
Ordering Reference (Plated Steel)	Reference Diameter	Minimum Thickness	External Diameter
16SW	M16	3.7	25.5
20SW	M20	3.9	32.5
25SW	M25	3.9	40.0
32SW	M32	3.9	43.5
40SW	M40	3.9	64.5
50SW	M50	3.9	80.0
63SW	M63	3.9	100.0
75SW	M75	3.9	112.0
90SW	M90	4.1	135.0
100SW	M100	4.1	144.6
150SW	M115	4.1	159.0

**Dimensions are displayed in millimetres unless otherwise stated**

Ordering Reference (Brass)	Reference Diameter "A"	Minimum Thickness	External Diameter "B"
16SW	M16	0.144	0.995
20SW	M20	0.152	1.268
25SW	M25	0.152	1.560
32SW	M32	0.152	1.697
40SW	M40	0.152	2.516
50SW	M50	0.152	3.120
63SW	M63	0.152	3.900
75SW	M75	0.152	4.368
90SW	M90	0.159	5.265
100SW	M100	0.159	5.639
115SW	M115	0.159	6.201

**All dimensions are in inches unless otherwise stated**



## NPT Serrated Washers Table

NPT - Serrated Washers			
Ordering Reference (Plated Steel)	Reference Diameter	Minimum Thickness	External Diameter
050NPTSW	1/2" NPT	3.9	32.5
075NPTSW	3/4" NPT	3.9	40.0
100NPTSW	1" NPT	3.9	43.5
125NPTSW	1-1/4" NPT	3.9	64.5
150NPTSW	1-1/2" NPT	3.9	80.0
200NPTSW	2" NPT	3.9	100.0
250NPTSW	2-1/2" NPT	3.9	112.0
300NPTSW	3" NPT	4.1	135.0
350NPTSW	3-1/2" NPT	4.1	144.6
400NPTSW	4" NPT	4.1	159.0
Dimensions are displayed in Millimetres unless otherwise stated			

Ordering Reference (Brass)	Reference Diameter "A"	Minimum Thickness	External Diameter "B"
050NPTSW	1/2" NPT	0.152	1.268
075NPTSW	3/4" NPT	0.152	1.560
100NPTSW	1" NPT	0.152	1.697
125NPTSW	1-1/4" NPT	0.152	2.516
150NPTSW	1-1/2" NPT	0.152	3.120
200NPTSW	2" NPT	0.152	3.900
250NPTSW	2-1/2" NPT	0.152	4.368
300NPTSW	3" NPT	0.159	5.265
350NPTSW	3-1/2" NPT	0.159	5.639
400NPTSW	4" NPT	0.159	6.201
All dimensions are in inches unless otherwise stated			





